

## MIG Bulk<sup>(B)</sup>

### Bulk Packaged Consumables Savings Center

Bulk packaged high-volume MIG consumables represent a 3% savings over our standard point-of-purchase packaging. It's a great way to pass along savings to your larger use accounts and reduce handling and space requirements. Save on consumables for the following high-volume products: GA-20C, M-Series, Roughneck®, Spoolmatic®, XR™-A & XR™-W; XR-Edge™, and XRM-15 & XRM-30.

*Order Note: You must use the standard 6-digit part number followed by the letter-B to receive the bulk packaging.* Example: **#000 067B**

Part #	Description	Quantity
<b>050 622B</b>	Nozzle, .625 (15.9 mm) x 1-5/8 lg	25
<b>169 715B</b>	Nozzle, slip .500 (12.7 mm) flush	10
<b>169 724B</b>	Nozzle, slip .500 (12.7 mm) .125 recess	10
<b>169 725B</b>	Nozzle, slip .625 (15.9 mm) .125 recess	10
<b>169 726B</b>	Nozzle, slip .625 (15.9 mm) flush	10
<b>199 618B</b>	Nozzle, scr .625 (15.9 mm) heavy-duty	10
<b>000 067B</b>	Tip, contact scr .030 (0.8 mm) wire x 1.125	100
<b>000 068B</b>	Tip, contact scr .035 (0.9 mm) wire x 1.125	100
<b>000 069B</b>	Tip, contact scr .045 (1.2 mm) wire x 1.125	100
<b>087 299B</b>	Tip, contact scr .023 (0.6 mm) wire x 1.125	100
<b>094 260B</b>	Tip, contact slip .047 (1.2 mm) wire x 4.000	100
<b>135 424B</b>	Tip, contact .047/61 (1.2/1.5 mm)	100
<b>135 425B</b>	Tip, contact .062/81 (1.5/2.1 mm)	100
<b>135 428B</b>	Tip, contact .030/41 (0.8/1.0 mm)	100
<b>135 430B</b>	Tip, contact .035/52 (0.9/1.3 mm)	100
<b>206 189B</b>	Tip, contact FasTip .052 (1.3 mm) or 3/64 (1.2 mm) alum wire	100
<b>169 728B</b>	Adapter, contact tip	25
<b>210 664B</b>	Diffuser, 1/4 in recess for Fastip contact tips	10



#000 067B



#000 068B



#000 069B



#087 299B



#169 715B



#169 726B



#169 728B

## Optional M-Series Gun Nozzles and Tips

Part #	Description	Quantity
	<b>M-25 and M-40 Tapered Nozzles</b>	
<b>176 243</b>	Nozzle, Tapered 3/8 in (9.5 mm)	1
<b>178 386</b>	Nozzle, Tapered 11/32 in (8.7 mm)	1
	<b>M-25 and M-40 Tapered Contact Tips (1/4 in OD x 1.312 in)</b>	
<b>176 797</b>	Contact Tip, Tapered .030 in (0.8 mm)	10
<b>176 793</b>	Contact Tip, Tapered .035 in (0.9 mm)	10
<b>176 794</b>	Contact Tip, Tapered .045 in (1.2 mm)	10
	<b>M-25 and M-40 Heavy-Duty Spray Contact Tips (5/16 in OD x 1.125 in)</b>	
<b>187 117</b>	Contact Tip, Heavy Duty .035 in (0.9 mm)	25
<b>187 118</b>	Contact Tip, Heavy Duty .045 in (1.2 mm)	25

