

Circuit Breakers Supplementary Protector Manual Reset (Thermal)

Part #	Poles	Amps	Volts	Terminals	Group
011 244	1	2	250 VAC/28 VDC	Friction, 1/4"	B
053 283	1	3	250 VAC/28 VDC	Friction, 1/4"	B
089 807	1	205	250 VAC/50 VDC	Friction, 1/4"	A
123 745	1	4	250 VAC/50 VDC	Friction, 1/4"	B
083 431	1	5	250 VAC/50 VDC	Friction, 1/4"	A
161 078	1	7	250 VAC/50 VDC	Friction, 1/4"	A
115 427	1	25	250 VAC/50 VDC	Friction, 1/4"	A
083 432	1	10	250 VAC/50 VDC	Friction, 1/4"	A
093 995 ¹	1	15	250 VAC/50 VDC	Friction, 1/4"	A
139 266	1	15	250 VAC/50 VDC	Friction, 1/4"	A
093 996	1	20	250 VAC/50 VDC	Friction, 1/4"	A
168 057	1	20	250 VAC/50 VDC	Friction 90°	A
117 501	1	40	250 VAC/32 VDC	Screw 90°	A
220 595	1	1.5	250 VAC/28 VDC	Friction, 1/4"	B

¹ROHS compliant



#053 283



#139 266

Diodes

Part #	Amps	Volts	Polarity	Stud Size	Length
406 170-003	10	300	Straight	1/4"	1-1/2"
087 998	85	300	Straight	1/4"	5-1/2"
087 999	85	300	Reverse	1/4"	5-1/2"
037 305	150	300	Straight	3/8"	5-1/2"
037 306	150	300	Reverse	3/8"	5-1/2"
037 956	275	300	Straight	3/4"	7"
037 957	275	300	Reverse	3/4"	7"
037 157	275	250	Straight	3/4"	7"

Important: When ordering always determine correct polarity. See illustration at right

